



MIDWAY PARTY RENTAL, INC.
 2110 Gilbert Av, St. Paul, MN 55104
651-644-0004



CAUTION!
 Requires dedicated
 20 AMP electric
 circuit!

Food Warmer Display Case

GRHDH MODELS (Humidified): The GRHDH Models (Humidified) are similar to the GRHD Models (non-humidified) but come equipped with a thermostatically controlled, adjustable humidity system. A 3 or 6 quart (2.8 or 5.7 liter) capacity heated water in the base provides humidity to extend food holding time up to four hours.

ELECTRICAL RATING CHART:

120	2005	1.67	NEMA 5-20P	200 lbs (91 kg)
200-230CE	2141	9.3	CEE 7/7 shuko	200 lbs (91 kg)
220	1959	8.9	CEE 7/7 shuko	200 lbs (91 kg)
230-240CE	2027	8.4	BS 1363	200 lbs (91 kg)
240	2027	8.4	BS 1363	200 lbs (91 kg)

SPECIFICATIONS:

Width: 26" or 660 mm
 Length: 46 3/8" or 1178 mm
 Height: 30" or 762 mm

OPERATION CAUTIONS AND WARNINGS:

1. To prevent any injury or damage to the unit, do not pull unit by the power cord.
2. To prevent any injury, discontinue use if power cord is frayed or worn.
3. To prevent any injury, do not place food directly on glass or stainless steel surfaces. Food product must be wrapped or boxed.
4. Do not use food pans, ceramic dishes or abrasive materials on heated glass shelves. Food pans, ceramic dishes and abrasive materials may scratch the glass shelf marring its appearance and making it susceptible to dirt accumulation.
5. It is recommended that glass shelves be used for food products contained in disposable paper or plastic containers or wrapping.

DIRECTIONS:

1. Plug cabinet into a properly grounded electrical outlet of the correct voltage, size and plug configuration.
2. Remove the center slotted pan divider from the water trough.
3. Turn the Power Switch to the ON position. See Figure 12
4. Rotate the Humidity Selector Control to the desired position. The green Humidity On Indicator will light up to show that humidity is on. The red Low Water Indicator will light when the water trough is empty.
5. Fill the water trough with softened or distilled water. The trough has a 3 quart (2.8 liter) capacity. If the red Low Water Indicator is on, press the Reset Button.
 NOTE: use of softened or distilled water is recommended to preserve the life of electrical and mechanical components. If hard water is used, the trough will require periodic cleaning and deliming.
6. Re-install the center Pan Divider.
 NOTE: when the red Low Water Indicator lamp is lit, add water to the reservoir and press the Reset Button.
7. Allow unit 30 minutes to reach operating temperature.
8. At the end of the day or shift, turn unit off and allow to cool down. Remove and clean water trough.

